




G1 V0

Single-Use Temperature data logger




Built-in USB Connector
Directly plug into PC, No cable required

IP67 Protection Class
Food-safety and water-proof packaging


Integrated PDF Generating
Software on-board, no software required

Qualified for Air Transport Monitoring
RTCA/DO-160G Approved,
Qualified for air transport



Were especially developed for monitoring temperature-sensitive products throughout the entire cold chain.

Products can be programmed according to customer needs



Using Plustrace-G1



01

Push START/STOP button to start



02

Put the started logger G1 to anywhere of your shipment



03

Connect to Pc USB port



04

Directly get the PDF report automatically

SPECIFICATION

Data logger type	Single use
Temperature range	-30°C to +70°C (-22°F to 158°F)
Accuracy	±0.5°C/0.9°F
Resolution	0.1°C/°F
Storage capacity	32000 Readings
Life/Battery	18 months/3V CR2032
Measurement interval	10 minutes (Customizable)
Recording time	60 Days (Customizable)
Startup method	Push start
Stop method	Push stop or stop by plug into usb port
Alarm type	High & Low Alarm
Protection class	IPE67/NEMA 6
Dimensions	75mm x 30mm x 4.5mm [L x W x H]
Weight	Approx 15g
Certified	EN12830, CE, RoHS, NIST
Calibration certificate	Nvlap NIST traceable (United States)
Software	Self -generated, no software required
Report	Adobe PDF graphics
Automatic report	PDF
PC connection	USB2.0
Delivery contents	Dispatch documents, certificate



Plustrace Technology co.,Ltd

E-mail: info@plustrace.com

Address: Building 2, LGXC, Jinshui Rd, Zhengzhou, 450018, PR China

Cel: +86 18613716048

Phone: +86 371 61317899

www.plustrace.com